



ORION 15-15/25

Type	15-15/25
System	Three-phase
Input voltage variation	+15/-25 %
Rated power	15 kVA
Input voltage range	300-460 V
Max input current	29 A
Output voltage	400 V
Rated output current	22 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	14 ms/V
Dimensions WxDxH	410x680x1200mm
Weight	165 kg



This image is indicative only.

Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz \pm 5% or 60Hz \pm 5%
Output voltage accuracy	\pm 0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Up to 45kVA \pm 15% natural ventilation From 60kVA \pm 15% aided with fans
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital multimeter
Installation	Indoor
Overvoltage protection	Output class II surge arrestors (over 60kVA \pm 15%)

Optional Accessories

Interrupting devices - INPUT	DI 32 - INPUT
Interrupting devices - OUTPUT	DI 25 - OUTPUT
Load protection against over/undervoltage	PS 25
CAM	CAM32
Input three-phase isolation transformer DYN11	DYN11 36A
SPD Surge arrestors	SPD INPUT CLASS I 25/4
SPD Surge arrestors	SPD OUTPUT CLASS II 20/4